

UV-NVR301-04X-P4

NVR for IP cameras

Easy range

4 CH video / Ultra Compression 265

4 PoE Channels

Maximum resolution 8 Mpx

Supports 1 hard disk



Uniview

NVR for IP cameras

Easy range

4 CH

80 Mbps bandwidth supported

Maximum resolution 8 Megapixel

Supports smart features

Smart Intrusion Prevention on 4 channels

Compression Ultra265/H.265/H.264

VGA and HDMI 4K output

Mouse

Space for 1 HDD

4 PoE ports IEEE802.3af/at

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	Uniview
Range	Easy
Inputs for IP cameras	LAN port up to 4 channels
Power over Ethernet	4 PoE IEEE802.3at(max.54 port switch W)
IP compatible cameras	UNIVIEW, ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	Ultra H.265 / H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Total bandwidth	80 Mbps downstream / 64 Mbps upstream
Main Stream recording	4K / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
Decoding	2x4K @ 30fps / 3x5MPx @ 30fps / 4x4MPx @ 30fps
Intelligent functions	People Counting, Face Detection, Intrusion Detection, Line Crossing, Scenery Change, Blur Detection, Auto Tracking, Removed object, Abandoned object
Smart Intrusion Prevention	Available at 4 channels
Recording method	Manual, programmed, motion detection
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	1 x USB 2.0 / 1 x USB 3.0 / 1 x RJ45 (Ethernet)
Remote access	EZStation Web Browser, Smartphone App and PC Software
Power	DC 48 V
Dimensions / Weight	47(A) x 260(An) x 240 (Fo) mm / 1Kg