

AXIS Q1786-LE Network Camera

Robust, first-class 4 MP video with 32x optical zoom

AXIS Q1786-LE Network Camera is an all-integrated camera delivering 4 megapixel resolution and 32x optical zoom for easy and flexible installation at any distance as well as detailed video for identification. With a wide temperature range, impact resistance and IP66, IP67 and NEMA 4X ratings, this robust and reliable camera is ready for tough environments. Lightfinder, Forensic WDR and OptimizedIR with 80 m (262 ft) range ensure details in challenging light conditions and darkness. AXIS Q1786-LE offers built-in analytics for proactive surveillance, corridor format and audio in for video with sound. Furthermore, Axis Zipstream saves bandwidth while keeping high video quality.

- > **4 MP / Quad HD 1440p at up to 60 fps**
- > **-40 °C to 60 °C (-40 °F to 140 °F)**
- > **OptimizedIR with 80 m (262 ft) range**
- > **Electronic Image Stabilization**
- > **AXIS Guard Suite included**



AXIS Q1786-LE Network Camera

Camera		IR illumination Autofocus
Image sensor	1/1.8" progressive scan RGB CMOS	
Lens	4.3–137 mm, F1.4–4.0 Horizontal field of view: 60°–2.3° Vertical field of view: 39°–1.3° Autofocus, auto-iris, automatic day/night Thread for 62 mm filters, max filter thickness: 5 mm	Event triggers Analytics, edge storage events Supervised external input, virtual inputs through API, shock detection, audio detection MQTT subscribe
Day and night	Automatically removable infrared-cut filter in day mode and infrared-pass filter 720 nm in night mode	Event actions Pre- and post-alarm video buffering File upload: FTP, SFTP, HTTP, HTTPS, network share and email MQTT publish Notification: email, HTTP, HTTPS, TCP and SNMP trap
Minimum illumination	Color: 0.18 lux at 50 IRE F1.4 B/W: 0.04 lux at 50 IRE F1.4 0 lux with IR illumination on	Data streaming Event data
Shutter speed	1/100000 s to 2 s	Built-in installation aids Remote zoom, pixel counter, leveling assistant, autorotation
System on chip (SoC)		Analytics
Model	ARTPEC-6	Applications Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, gatekeeper Supported AXIS Perimeter Defender, AXIS Cross Line Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Memory	1024 MB RAM, 512 MB Flash	Cybersecurity
Video		Edge security Software: Signed firmware, brute force delay protection, digest authentication, password protection
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Network security IEEE 802.1X (EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Resolution	2560x1440 to 160x120 Maximum pixel density with 32x optical zoom: 25 m (82 ft): 2551 px/m 50 m (164 ft): 1275 px/m 250 m (820 ft): 255 px/m	Documentation <i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Frame rate	With WDR: Up to 25/30 fps (50/60 Hz) in all resolutions Without WDR: Up to 50/60 fps (50/60 Hz) in all resolutions	General
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	Casing IP66-, IP67-, and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure with integrated dehumidifying membrane, IK08 impact-resistant glass front window, weathershield with black anti-glare coating Color: White NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, defogging, white balance, day/night threshold, exposure mode, exposure zones, compression, mirroring of images, electronic image stabilization, barrel distortion correction, text and image overlay, dynamic text and image overlay, privacy masks Rotation: auto, 0°, 90°, 180°, 270° including Corridor Format Scene profiles: forensic, vivid, traffic overview, backlit entrance	Sustainability PVC free, 2% recycled plastic
Pan/Tilt/Zoom	32x optical zoom, preset positions	Memory 1024 MB RAM, 512 MB Flash
Audio		Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 8.6 W, max 12.95 W 20–28 V DC, typical 8.6 W, max 13.8 W 20–24 V AC, typical 12.6 V A, max 20 V A
Audio streaming	Audio in, simplex Two-way audio via edge-to-edge technology	Connectors Shielded RJ45 10BASE-T/100BASE-TX PoE IDC punchdown connector DC Power connector Terminal block for two configurable supervised inputs / digital outputs (12 V DC output, max. load 50 mA) 3.5 mm mic/line in
Audio encoding	AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM Configurable bit rate	IR illumination Optimized IR with power-efficient, long-life 850 nm IR LED's with adjustable angle of illumination and intensity. Range of reach 30 m (98 ft) in wide field of view and 80 m (262 ft) in full tele view, or more depending on the scene
Audio input/output	Automatic gain control, external microphone input, line input, digital input with ring power, balanced microphone, balanced input Network speaker pairing	Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Network		Operating conditions -40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
System integration		
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specification at onvif.org	
Onscreen controls	Electronic image stabilization Day/night shift Defogging Wide dynamic range	

Approvals	<p>EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35, EAC</p> <p>Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, EN/IEC 62471 IS 13252</p> <p>Environment EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IP67, IEC/EN 62262 IK10 body, IK08 glass, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9)</p> <p>Network NIST SP500-267</p>	<p>Included accessories Installation guide, Windows® decoder 1-user license, connector kit, Resistorx® L-key RJ45 patch cable</p>
Dimensions	<p>Length: 386 mm (15 3/16 in) ø 147 mm (5 13/16 in)</p>	<p>Optional accessories AXIS T8604 Media Converter Switch AXIS T91A47 Pole Mount, AXIS T94P01B Corner Bracket AXIS Q17 Front Window Kit B (IK10 impact-resistant plastic front window) For more accessories, see axis.com</p>
Weight	2.4 kg (5.3 lb)	<p>Video management software AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms</p>
		<p>Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese</p>
		<p>Warranty 5-year warranty, see axis.com/warranty</p>